

Screen Size 4:3		Throw distance	
Diagonal*	Width*	Min*	Max*
30	24	34	41
60	48	70	84
80	64	93	112
100	80	117	140
120	96	140	169
150	120	176	211
200	160	234	282
300	240	352	423

Throw ratio: 1.5 - 1.7:1 (distance:width)

\*Measured in inches



- 2,500 ANSI Lumens
- Native XGA Resolution
- 7.2 lbs
- 2 RGB inputs and 1 RGB Output
- Component / Composite / S-Video Inputs
- PC less presentation
- Transition Detector
- Digital Gamma Correction
- Auto Vertical Keystone Correction
- Remote Control with "My Buttons"
- 802.11 b/g Connect & Present with 4pc's wirelessly
- 34 dB (Whisper Mode)
- Supplied Soft Case
- My Screen / My Memory
- Whiteboard Mode
- Blackboard Mode
- Approx. 3,000 hrs (Whisper Mode)
- Security Bar
- Kensington Security Slot
- RJ-45 Port
- Audio Input / Output
- Input Source Naming
- Network Control, Maintenance & Scheduling
- USB 2.0 & SD removable memory reader

## SPECIFICATIONS

<b>Model name</b>	CP-X268A series		
Liquid crystal panel structure	0.63" polysilicon active-matrix TFT x 3		
Number of pixels	786,432 pixels		
Resolution	Video	540 TV lines	
	RGB	1024 dots X 768 lines	
Colors	16.7 million colors		
Aspect ratio	Native 4:3/16:9 compatible		
Lens	F1.7 - 1.9 manual zoom 1:1-2		
Throw ratio (distance:width)	1.5 - 1.7:1		
Lamp	200W UHB		
Brightness	2,500 ANSI lumens		
Expected lamp life	Approx. 3,000 hrs (Whisper Mode) Approx. 2,000 hrs (Natural Mode)		
Contrast ratio	500:1		
Speakers	1W x 1		
Power supply	AC100-120V/AC220-240V 50/60Hz		
Power consumption	330W		
Operating temperature	5°C ~ 35°C (41°F ~ 95°F)		
Input signals	RGB	VGA, SVGA, XGA, SXGA, UXGA, MAC13", MAC16"	
	Composite video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N	
	Component video	480i, 576i, 480p, 720p, 1080i	
Acoustic noise level	39dB (34dB in whisper mode)		
H sync	15kHz ~ 106kHz		
V sync	50Hz ~ 120Hz		
Vertical keystone correction	Digital keystone +/- 30°		
Approvals	UL60950 / C-UL, FCC Part15, Class B, CE, EN60950		
Input/Output terminals	RGB input	Analog RGB	15-pin D-sub connector x 2
	RGB output	RGB	15-pin D-sub connector x 1
	Video input	S-video	Mini DIN 4-pin connector x 1
		Composite video	RCA jack x 1
		Component video	RCA jack x 3
	Audio	Input	Stereo mini jack x 2, RCA jack (L/R) x 1
		Output	Stereo mini jack x 1
	Others	SD Card, USB 2.0 Memory (jpeg, bmp, png, MPEG4)	
	Control terminals	9-pin D-sub connector x 1 (RS-232 control)	
		USB connector (USB mouse) x 1	
Chassis	Wireless	802.11 b/g	
	Ethernet	RJ-45 Port / 100BASE-T	
	Dimensions	12.0" x 4.2" x 9.8" (W x H x D)	
	Weight	7.2 lbs.	
	Supplied accessories	Remote Control, Batteries (AA), RGB Cable, RCA Video Cable, Power Cord, Multiple Language Operator / Safety Manual, Soft Case, Security Label, SD Wireless Card	
Replaceable parts	Lamp	CPX260LAMP	
	Remote Control	HL02221	
	Filter	NJ22222	